

Led Down Light



Product: Led Down Light GCTD

Model: GCTD

## Features

- - Standard Colors: White, Black, Brush Nickel, Chrome(Can Custom Colors)
- - Air Tight & IC Rated
- - High Efficiency
- - 3CCT Adjusted by DIP Switch: 30K/40K/50K
- - 5CCT Adjusted by DIP Switch: 27K/30K/40K/50K/60K
- - 3CCT Adjusted by DIP Switch and Wall Switch Control: 30K/40K/50K
- - 5CCT Adjusted by DIP Switch and Wall Switch Control: 27K/30K/40K/50K/60K
- - CCT Adjustable and Power Changeable: 27K/30K/40K/50K/60K 25W/35W/45W

## Details

PowerLuminous EfficacyDefault Driver InputColor TemperatureLEDPower FactoryInput VoltageTHDWeightDimensionHousing	30W-55W 80 100-347 V 	2700-6500 2700-6500 SMD 100-347 V <20% 2.3 Pounds 152mm (6")-254mm (10")	145mm (6")-175mm (6 7/8")
Default Driver Input Color Temperature LED Power Factory Input Voltage THD Weight Dimension	100-347 V	SMD 100-347 V <20% 2.3 Pounds 152mm (6")-254mm	145mm (6")-175mm (6 7/8")
Color Temperature LED Power Factory Input Voltage THD Weight Dimension		SMD 100-347 V <20% 2.3 Pounds 152mm (6")-254mm	145mm (6")-175mm (6 7/8")
LED Power Factory Input Voltage THD Weight Dimension	188mm(7 3/8")-280mm(11")	SMD 100-347 V <20% 2.3 Pounds 152mm (6")-254mm	145mm (6")-175mm (6 7/8")
Power Factory Input Voltage THD Weight Dimension	188mm(7 3/8")-280mm(11")	100-347 V <20% 2.3 Pounds 152mm (6")-254mm	145mm (6")-175mm (6 7/8")
Input Voltage THD Weight Dimension	188mm(7 3/8")-280mm(11")	<20% 2.3 Pounds 152mm (6")-254mm	145mm (6")-175mm (6 7/8")
THD Weight Dimension	188mm(7 3/8")-280mm(11")	<20% 2.3 Pounds 152mm (6")-254mm	145mm (6")-175mm (6 7/8")
Weight Dimension	188mm(7 3/8")-280mm(11")	2.3 Pounds 152mm (6")-254mm	145mm (6")-175mm (6 7/8")
Dimension	188mm(7 3/8")-280mm(11")	152mm (6")-254mm	145mm (6")-175mm (6 7/8")
	188mm(7 3/8")-280mm(11")		145mm (6")-175mm (6 7/8")
Housing			
Beam Angle	60°-80°		
Lens	Glass		
Mounting			
Operation Temperature			
Humidity			
Finish			
IP rated			
Certificate		UL,DLC.LM80	
Material Usage			
Driver Class	Constant Current Body		
	Mounting peration Temperature Humidity Finish IP rated Certificate Material Usage	Mounting peration Temperature Humidity Finish IP rated Certificate Material Usage	Mounting peration Temperature Humidity Finish IP rated Certificate UL,DLC.LM80 Material Usage

## Certifications

c**(**₩L)

LISTED E487752

