



Led Down Light



Product: LED Down Light GCTD

Model: GCTD4/GCTD6/GCTD8

Features

- - Standard Colors: White, Black, Brush Nickel, Chrome (Can Custom Colors)
- - Air Tight & IC Rated
- - High Efficiency
- - 3CCT Adjusted by DIP Switch: 30K/40K/50K
- - 5CCT Adjusted by DIP Switch: 27K/30K/40K/50K/60K
- - 3CCT Adjusted by DIP Switch and Wall Switch Control: 30K/40K/50K
- - 5CCT Adjusted by DIP Switch and Wall Switch Control: 27K/30K/40K/50K/60K
- - CCT Adjustable and Power Changeable: 27K/30K/40K/50K/60K 25W/35W/45W

Details

Item	Model	Led Recessed Ceiling		
General Performance	Power	10W-40W		
	Luminous Efficacy	80		
	Default Driver Input	100-347 V		
	Color Temperature	2700-6500		
	LED	SMD		
Electrical	Power Factory			
	Input Voltage	100-347 V		
	THD	<20%		
Physical	Weight		2.3 Pounds	
	Dimension	130mm(51/8")-238mm(9 3/8")	102mm (4")-203mm (8)	125mm (5")-193mm (75/8")
	Housing			
	Beam Angle	60°		
	Lens	Glass		
	Mounting			
	Operation Temperature			
	Humidity			
	Finish			
	IP rated			
Certificate	Certificate	UL,DLC.LM80		
	Material Usage			
	Driver Class	Constant Current Body		

Certifications



LM80



ErP



IP65

