

LED LINEAR STRIP LIGHT

STR-4FT-M50W-CCT | STR-8FT-M100W-CCT

DESCRIPTION

4FT/8FT Led Linear Strip Light | Wattage Selectable | CCT Selectable | Linkable | Dimming



CONSTRUCTION

00

Metal Housin | White Frosted Cover | Plastic End Caps

ELECTRICAL

Long-life LEDs, coupled with a high-efficiency driver, provide superior illumination for extended service life. Available as 120-277V input.

INSTALLATION Surface Mounting or V-Hook/Chain Mounting

LINKABLE

These can link together. 4FT: up to 10 pieces. 8FT: up to 5 pieces.

APPLICATIONS

Warehouse/Manufacturing Facilities/Storage/Retail/Aisles. Suitable for dry and damp indoor locations. Working temperature -4°F to 113°F (-20°C to 45°C).

DIMMING Continuous dimming (0-10V) comes standard.

LISTING

ETL, DLC

WARRANTY

5 Years Limited Warranty, Rated for 50,000 hours.

FEATURES	
Size	4FT / 8FT
5Wattage	M50W / M100W
5CCT	3500K/4000K/5000K/ 5700K/6500K (Selectable)
Efficiency	130-150lm/W
Lumens	3750-13000lm
Beam Angle	180°
Input Voltage	120-277V AC
Frequency Range	50/60Hz
CRI	>80
PF	>0.9
THD	<=20%
Dimming	0-10V DC
Lifetime	50,000 hours
Operating Temperature	-4°F to 113°F (-20°C to 45°C)

0

0



LED LINEAR STRIP LIGHT

STR-4FT-M50W-CCT | STR-8FT-M100W-CCT

ORDERING INFORMATION

Model	Lenght	Wattage	Voltage	Lumens	Efficacy	сст	Dimming	Dimensions
		25W,		3750lm,		3500K,		
		30W,		4350lm,		4000K,		
STR-4FT-M50W-CCT	4FT	35W,	120-277V	4900lm,	130-150lm/W	5000K,	0-10V	46.5″L x 2.48″W x 2.84″H
		40W,		5400lm,		5700K,		
		50W		6500lm		6500K		
		(Selectable)				(Selectable)		
		50W,		6500lm,		3500K,		
		60W,		7800lm,		4000K,		
STR-8FT-M100W-CCT	8FT	70W,	120-277V	9100lm,	130-150lm/W	5000K,	0-10V	92.9"L x 2.48"W x 2.84"H
		80W,		10400lm,		5700K,		
		100W		13000lm		6500K		
		(Selectable)				(Selectable)		

WEIGHT INFORMATION

4FT(1Pcs)	Pcs / Carton	Gross Weight	8FT(1Pcs)	Pcs / Carton	Gross Weight
1.41kg / 3.111bs	6 pcs	11.71kg / 25.82lbs	2.82kg / 6.23lbs	4 pcs	16.28kg / 35.89lbs

PHYSICAL SPECIFICATIONS

